



## China 608z Bearing Supplier



### NSK Koyo NACHI NTN 62/22 6203 Dull SKF Bearing 6203

Bearing No. 62/22

62/22 Bearing 2D drawings and 3D CAD models

Size	22x50x14 mm
Bore Diameter	22 mm
Outer Diameter	50 mm
Width	14 mm
d	22 mm
D	50 mm
B	14 mm
C	14 mm
r min.	1 mm
da min.	28 mm
Da max.	44 mm
ra max.	1.0 mm
Weight	0.120 Kg
Basic dynamic load rating (C)	13,9 kN
Basic static load rating (C0)	6,95 kN
(Grease) Lubrication Speed	13000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	22 mm
Outside Diameter	50 mm
Width	14 mm
Fillet Radius/Chamfer	1 mm
Dynamic Load Rating	13,900 N
Static Load Rating	6,950 N



## China 608z Bearing Supplier

Limiting Speed - Grease	14,000 rpm
Limiting Speed - Oil	17,000 rpm
Factor $f_0$	13.1
Radial Clearance	0.005 to 0.020 mm
$d_a$ (min)	28 mm
$D_a$ (max)	44 mm
$r_a$ (max)	1 mm